

BUILDING UNDERLAY

SELECTED FLOORING

SELECTED CRAFTSTONE
VENEER OVER CRAFTSTONE
ADHESIVE MORTAR ON 9mm
CRAFTSTONE FCB FIXED ACCORDING
TO MANUFACTURERS
CONSTRUCTION DETAILS

CAVITY SYSTEM

TIMBER CAVITY PACKER
MUST BE SET TO A FALL OF 5°

CAVITY CLOSER

MIN. 15mm

MIN. 175mm TO UNPAVED GROUND
MIN. 100mm TO PAVED GROUND

SUBFLOOR LINING TO CLOSE OFF
SUBFLOOR FROM WALL CAVITY

15

DPC

FRAMING

SUB-FLOOR JOIST

H5 TIMBER PILE



**CRAFT
STONE**

Real Stone Made Easy

TYPICAL TIMBER SUB FLOOR DETAIL

22/11/23
ISSUED

COPYRIGHT PETROS HOLDINGS LIMITED (T/A CRAFTSTONE NEW ZEALAND)
CRAFTSTONE NEW ZEALAND ACCEPTS NO LIABILITY FOR DRAWINGS SUBMITTED TO COUNCIL

61 HILLSIDE RD, WAIRAU VALLEY, AUCKLAND, NEW ZEALAND - P: 0800 63 88 99

WWW.CRAFTSTONE.CO.NZ

VER.5.1

B4
SHEET